



Light Duty Castors

BOLT HOLE FITTING

- For loads up to 60kg per castor.
- Available in Swivel and Braked forks.
- A heavy flat washer is pressed on the headrace for flush mounting. This also keeps out dust and water.
- Expanding fittings available - see chart below.
- The non-marking rubber (TPR) wheels are fitted with thread guards and precision ball bearings for quiet and smooth running.
- Suitable for a wide range of shop fittings, medical equipment, office and home furniture.



WLU50/H










WLU50/H-B



WLR75/H



WLR75/H-TB

CODE	 (mm)	 (mm)		 (kg)		 (mm)	Swivel Braked	 (mm)
WLU50/H	50	18	Urethane	40kg	Plain	67	S	10
WLU50/H-B	50	18	Urethane	40kg	Plain	67	B	10
WLR75/H	75	25	Rubber	60kg	Ball	106	S	10/12
WLR75/H-TB	75	25	Rubber	60kg	Ball	106	TB	10/12
WLR100/H	100	25	Rubber	60kg	Ball	134	S	10/12
WLR100/H-TB	100	25	Rubber	60kg	Ball	134	TB	10/12

Expanding Fittings Available: (Tube I.D. mm) (add to code)	
round	square
	19S
19R	22S
22R	27S
27R	32S
31R	36S



WLR100/H



WLR100/H-TB