



# Pneumatic Wheels - Steel Rims

- For loads up to 260kg per wheel.
- Strong one piece fully welded rims with large 2" x 1", or 3/4", bearings.
- Medium duty, low speed wheels suitable for materials handling and jockey wheels.



FBSR100-B25  
-280/250 x 4










BW100-B25  
-410/350 x 4



FB1805  
-410/350 x 4



BW150-B19  
-400x 6

CODE	Rim							
								
	(mm)	(mm)	(mm)		(mm)	(mm)		
4"	BW100-B19 - 300 x 4	100	80	19.05	Ball	73	248	105kg
	BW100-B19 - 410/350 x 4	100	80	19.05	Ball	80	268	160kg
	BW100-B19 - 11/400 x 4	100	80	19.05	Ball	95	282	95kg
*Ball Bearing options B - 19.05, 25.4mm								
	FBSR100-B19 - 280/250 x 4	100	80	19.05	Ball	61	216	100kg
	FBSR100-B19 - 300 x 4	100	80	19.05	Ball	73	248	105kg
	FBSR100-B19 - 410/350 x 4	100	80	19.05	Ball	80	268	160kg
	FBSR100-B19 - 11/400 x 4	100	80	19.05	Ball	95	282	95kg
*Ball Bearing options B - 19.05, 25.4mm								
	FB1805 - 410/350 x 4	100	55	16.0	Ball	80	268	80kg
	FB1827 - 410/350 x 4	100	68	20.0	Ball	80	268	100kg
5"	BW125-B19 - 410/350 x 5	125	95	19.05	Ball	80	292	172kg
	BW125-B19 - 11/400 x 5	125	95	19.05	Ball	105	273	148kg
*Ball Bearing options B - 19.05, 25.4mm								
6"	BW150-B19 - 400 x 6	150	80	19.05	Ball	95	345	230kg
	BW150-B19 - 410/350 x 6	150	80	19.05	Ball	80	325	200kg
*Ball Bearing options B - 19.05, 25.4mm								
	BWW150-B19 - 13/500 x 6	150	80	19.05	Ball	127	318	200kg
	BWW150-B19 - 15/600 x 6	150	80	19.05	Ball	150	361	260kg
*Ball Bearing options B - 19.05, 25.4mm								

**NB** When ordering, state bearing size. eg. BW100B19 - 300x4 [19.05mm bearing]  
For rims only, see page 53