



Conveyor Systems

- Ball transfers enable the movement of goods in any direction [horizontally].
- Multi directional rollers are mounted on a shaft and enable products to move in any direction.



BT253-B



BT253-F



MTR50



SKW483

CODE	Description
BALL TRANSFERS	
BT253-B	Load capacity 50kg. Zinc plated pressing with hardened balls. 30.2mm high, 42mm diameter housing.
BT253-F	Load capacity 60kg. Flush mounted zinc plated pressing with hardened balls. 73mm flange diameter, 15mm high when mounted.
MULTI DIRECTIONAL ROLLERS	
MTR50	Load capacity 5kg. Acetal rollers. 50mm diameter. Connecting piece available to make continuous rollers.
MTR80	Load capacity 20kg. 80mm diameter Stainless axle and connecting piece available to make continuous rollers.
SKATE WHEEL	
SKW483	Load capacity 30kg. Zinc plated finish. 48mm diameter. 8mm bore.
MINI ROLL	
MR-ROLL	Robust galvanised steel track. Nylon roller diameter 28mm. Track width 35mm x 2376mm long.
XPANDAROLL	
XP-ROLL	A flexible mobile conveyor table. Skate wheels are ideal for self tracking. 450mm wide, 1.2 - 3.6 meters long. Adjustable height from 690mm - 1000mm



MR-ROLL



XPANDAROLL